

Simple, compact and cost-competitive with enhanced SSL performance. The Monimax 5000 CE offers unparalleled value.

Features

TCP/IP with SSL Support

Monimax 5000 CE includes built-in TCP/IP with Secure Socket Layers (SSL) for extra security while connected to the Internet. This new connectivity feature provides a direct connection without additional boxes, adaptors or converters. The result? A more affordable product that saves both time and money.

Capacity from 1,000 to 6,000 Notes

Customize a dispenser profile based on the volume of transactions at each Monimax 5000 CE site. This ATM is an ideal solution for multiple locations with various dispenser needs. Configuration can include the standard 1,000-note cassette or up to three optional 2,000-note cassettes for a maximum of 6,000 notes.

Quick Pick Lotto Software Ready

The 5000 CE is capable of being loaded with Linq 3's proprietary Quick Pick Lotto software. Quick Pick Lotto capability can be upgraded to existing CE models already installed, or added to new ATMs you order.

***Superior quality, security and value.
Only with Nautilus Hyosung.***

Now offering the most complete line of financial and retail ATMs.



Back-lit topper shown is an additional option.



The 5000 CE is Quick Pick Lotto Software-enabled.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX™ 5000 CE

System Control

- Embedded Windows Platform
- Intel® Xscale® processor
- Microsoft® Windows® CE

Customer Display

- 10.4" TFT LCD

Communication

- Dial-up or TCP/IP (SSL configurable)

Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Supports Two Languages

- English
- Spanish

Cash Dispensing

- 1,000-note cassette
- 2,000-note cassette
- Up to three cassettes (6,000 notes)

Printers

- 3.1" graphical thermal receipt printer
- Electronic journal

Security

- UL291 business hour
- Standard electronic safe lock
- Optional KABA Mas Cencen safe lock

Miscellaneous

- Guide lights
- Optional high-brightness topper

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: 32°F–104°F
- Humidity: 25%–86%

Dimension and Weight

- Height: 53.5" (1,360 mm)
- Width: 15.7" (400 mm)
- Depth: 24.8" (631 mm)
- Weight: 253.5 lbs (115 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Supports Quick Pick Lotto Software



Security mirrors

10.4" TFT LCD
customer display

- Ad-capable: 6 jpeg files

3.1" Graphic thermal
receipt printer

Capacity from
1,000- to 6,000-note
cash dispenser



Function keys

Card reader

Lit key pad

PCI Encrypting PIN pad



Contact your authorized Nautilus Hyosung distributor
or go to www.nhatm.com for more information.